



## PS-2316


### Product Description:

P-SHIELD® PS-2316 is an electrically conductive foam with a conductive acrylic adhesive on each side for shielding/grounding applications.

### Construction / Properties:

Property	Value	Test Method
Available Thicknesses	1.0 mm, 2.5 mm	QSP-726
Foam Thickness Tolerance	mm ± 20%	--
Adhesive Peel Strength (to SUS)	800 g/25mm	QSP-722
Surface Resistivity	<0.5 Ω/sq	QSP-741
Z-Axis Resistance	<0.5 Ω/in <sup>2</sup>	QSP-741
Shielding Effectiveness (10 MHz- 100 GHz)	70 – 100 dB	--
Recommended Application Specification	2 kg/square inch for 2 seconds	--
Continuous Use Conditions	-10 – 80 C	WI-8.2-13

### Shielding Effectiveness:



Specific tests should be performed by the end user to determine the product suitability for the particular application.

For Additional Information:

E-Mail: [sales@polymerscience.com](mailto:sales@polymerscience.com)

Toll Free: +1 888.533.7004

Web: [www.polymerscience.com](http://www.polymerscience.com)

Revision: 052316




## PS-2316

### Product Description:

P-SHIELD® PS-2316 is an electrically conductive foam with a conductive acrylic adhesive on each side for shielding/grounding applications.

### Features

- Superior Converting Properties
- Excellent Shielding Effectiveness
- RoHS and HF Compliant



Specific tests should be performed by the end user to determine the product suitability for the particular application.

For Additional Information:

E-Mail: [sales@polymerscience.com](mailto:sales@polymerscience.com)

Toll Free: +1 888.533.7004

Web: [www.polymerscience.com](http://www.polymerscience.com)

Revision: 052316