



## PS-2326

### Product Description:

P-SHIELD® PS-2326 is an aluminum foil coated on each side with an electrically conductive acrylic pressure sensitive adhesive to allow conductivity in the x, y and z-plane.

### Construction / Properties:

Property	Value	Test Method
Total Thickness	0.24 mm	QSP-726
Carrier	Aluminum Foil	--
Surface Resistivity	<0.05 $\Omega$ /sq	QSP-741
Z-Axis Resistance	<0.05 $\Omega$ /in <sup>2</sup>	QSP-741
Color	Dark Gray	Visual
Adhesive Peel Strength (to SUS)	>1200 g/25mm	QSP-722
Recommended Application Specification	2 kg/square inch for 2 seconds	--
Continuous Use Conditions	-10 – 80 C	WI-8.2-13

Specific tests should be performed by the end user to determine the product suitability for the particular application.

For Additional Information:

E-Mail: [sales@polymerscience.com](mailto:sales@polymerscience.com)

Toll Free: +1 888.533.7004

Web: [www.polymerscience.com](http://www.polymerscience.com)

Revision: 082316




## PS-2326

### Product Description:

P-SHIELD® PS-2326 is an aluminum foil coated on each side with an electrically conductive acrylic pressure sensitive adhesive to allow conductivity in the x, y and z-plane.

### Features

- Superior Converting Properties
- Good Conformability
- Good Tack
- Good Adhesion to Low Surface Energy Substrates
- Excellent Shielding Effectiveness
- RoHS and HF Compliant



Specific tests should be performed by the end user to determine the product suitability for the particular application.

For Additional Information:

E-Mail: [sales@polymerscience.com](mailto:sales@polymerscience.com)

Toll Free: +1 888.533.7004

Web: [www.polymerscience.com](http://www.polymerscience.com)

Revision: 082316