

## PS-1543

### Product Description:

P-THERM® PS-1543 is an ultra-soft silicone based thermally conductive gap filler with an embedded fiberglass support and polyester carrier.


### Construction / Properties:

Property	Value	Test Method
Color	Green	Visual
Carrier	Polyester Film	--
Thickness Range	0.5 mm - 5.0 mm	ASTM D374
Thermal Conductivity	3.0 W/m K	ASTM D5470
Thermal Impedance (at 30% Compression)	4.71 cm <sup>2</sup> /W	ASTM D5470
Dielectric Strength	386 V/mil	ASTM D149
Dielectric Breakdown Strength	>17 kV <sub>AC</sub>	ASTM D149
Hardness (Shore 00)	35	ASTM D2240

### Features:

- Excellent Thermal Conductivity
- Excellent Compression Characteristics
- Good Wet-Out
- Superb Flexibility
- Excellent Converting Properties
- RoHS and HF Compliant

Ultra-Soft Silicone  
with Embedded  
Fiberglass Support  
Polyester Film Carrier



Specific tests should be performed by the end user to determine the product stability for the particular application.

### For Additional Information:

E-mail: [sales@polymerscience.com](mailto:sales@polymerscience.com)  
Toll Free: +1 888.533.7004  
Web: [www.polymerscience.com](http://www.polymerscience.com)  
Revision: 022719